

# 角度付溝仕様一覧

φ40～φ60用

φ30以下用

φ30以下用 ( 15° ,30° ,60° ,85° )

φ30以下用 ( 0° )

2015年1月

角度	呼び	歯直角ピッチ	参考深度	参考セル容積
	(線=L)	(P mm)	(H μm)	(cm <sup>3</sup> /m <sup>2</sup> )
45°	20	1.2700	349	172
	25	1.0160	342	167
	30	0.8467	299	149
	36	0.7056	257	114
	40	0.6350	236	114
	45	0.5644	204	96
	50	0.5080	182	85
	55	0.4618	161	78
	60	0.4233	145	72
	65	0.3908	126	83
	70	0.3629	125	77
	75	0.3387	113	55
	80	0.3175	105	49
	85	0.2988	100	47
	90	0.2822	95	49
	95	0.2674	82	40
	100	0.2540	70	36
	105	0.2419		
	110	0.2309	65	33
	120	0.2117	59	29
130	0.1954	51	26	
140	0.1814	44	22	
150	0.1693	38	16	
160	0.1588			
170	0.1494			
180	0.1411	34	16	
190	0.1337			
200	0.1270	25	13	
210	0.1210			
220	0.1155			
230	0.1104	27	13	
240	0.1058			
250	0.1016	28	13	
300	0.0847	22	11	
350	0.0726	12	6	
400	0.0635	6	3	

角度	呼び	歯直角ピッチ	参考深度	参考セル容積
	(線=L)	(P mm)	(H μm)	(cm <sup>3</sup> /m <sup>2</sup> )
45°	20	1.2700	361	173
	25	1.0160		
	30	0.8467		
	36	0.7056	265	133
	40	0.6350		
	45	0.5644	204	97
	50	0.5080	184	87
	55	0.4618		
	60	0.4233	140	70
	65	0.3908		
	70	0.3629	125	57
	75	0.3387		
	80	0.3175		
	85	0.2988	100	47
	90	0.2822	92	48
	95	0.2674		
	100	0.2540	72	35
	105	0.2419		
	110	0.2309	62	28
	120	0.2117		
130	0.1954	48	23	
140	0.1814			
150	0.1693	37	19	
160	0.1588			
170	0.1494			
180	0.1411	35	16	
190	0.1337			
200	0.1270	31	17	
210	0.1210			
220	0.1155			
230	0.1104			
240	0.1058			
250	0.1016	25	14	
300	0.0847	23	11	
350	0.0726	16	8	
400	0.0635	11	7	

角度	呼び	歯直角ピッチ	参考深度	参考セル容積
	(溝仕様)	(P mm)	(H μm)	(cm <sup>3</sup> /m <sup>2</sup> )
15°	P0.08H6S	0.08	6	4
	P0.1H12S	0.1	12	6
	P0.1H16S	0.1	16	9
	P0.2H28S	0.2	28	11
	P0.2H24S	0.2	24	11
	P0.2H33S	0.2	33	16
	P0.25H40S	0.25	40	20
	P0.25H54S	0.25	54	26
	P0.3H62S	0.3	62	32
	P0.4H71S	0.4	71	37
	P0.4H82S	0.4	82	41
	P0.508H197S	0.508	197	98
30°	P0.2H15S	0.2	15	8
	P0.2H15S	0.2	15	9
	P0.3H17S	0.3	17	10
	P0.2H20S	0.2	20	10
	P0.25H40S	0.25	40	21
	P0.25H56S	0.25	56	27
	P0.3H62S	0.3	62	33
	P0.4H79S	0.4	79	37
	P0.4H72S	0.4	72	38
	P0.2H81S	0.2	81	40
60°	P0.7H144S	0.7	144	71
	P0.2H22S	0.2	22	10
	P0.127H47S	0.127	47	21
	P0.2H73S	0.2	73	36
85°	P0.508H190S	0.508	190	51
	P0.2H75S	0.2	75	34

角度	呼び	歯直角ピッチ	参考深度	1mm当面積
	(溝仕様)	(P mm)	(H μm)	(mm <sup>2</sup> )
0°	P0.1H7S	0.1	7	0.0042
	P0.2H8K	0.2	8	0.0063
	P0.1H11K	0.1	11	0.0065
	P0.15H22S	0.15	22	0.0073
	P0.125H12K	0.125	12	0.0076
	P0.1H15K	0.1	15	0.0083
	P0.1H18S	0.1	18	0.0086
	P0.125H19K	0.125	19	0.0114
	P0.2H18K	0.2	18	0.0128
	P0.2H20K	0.2	20	0.0131
	P0.125H21K	0.125	21	0.0132
	P0.2H22K	0.2	22	0.0154
	P0.2H29K	0.2	29	0.0180
	P0.2H32K	0.2	32	0.0180
	P0.2H34K	0.2	34	0.0190
	P0.2H43K	0.2	43	0.0219
	P0.2H42K	0.2	42	0.0233
	P0.3H41K	0.3	41	0.0260
	P0.3H47K	0.3	47	0.0299
	P0.3H44K	0.3	44	0.0303
P0.3H54K	0.3	54	0.0328	
P0.4H66K	0.4	66	0.0478	
P0.4H91K	0.4	91	0.0579	
P0.4H127K	0.4	127	0.0675	
P0.45H133K	0.45	133	0.0678	
P0.45H136K	0.45	136	0.0911	
P0.45H139K	0.45	139	0.0912	
P0.6H163K	0.6	163	0.1033	

※塗布条件、塗布液の物性により膜厚の差異が発生する場合がございます。

※一覧表に掲載していない仕様もございます。ご要望する仕様がない場合はお問い合わせ下さい。